

EMS Plant List

23rd November 2018

Issue 2.1



Plant List Overview

Surface Mount Assembly

- 2 x fully automated Surface Mount Lines with capacity up of 148,000 CPH and placements down to 01005"
- Line 1 = 38,000 CPH
- Line 2 = 110,000 CPH

Automated Optical Inspection (AOI)

- 1 x MEK Marantz AOI machine with top camera.
- 1 x MEK Marantz AOI machine with top and bottom camera.

PCB Cleaning

1 x Trident ZDO Aqueous PCB Cleaner


In Circuit Test

 1 x HP 3070 In Circuit Test (ICT) machine



Surface Mount Line 1

automation.



Maximum PCB Length	Part Number Capacity	Components Per Hour
500mm	160	38,000

■ Including, BGA, uBGA, QFN, CSP

■ Up to 100mm x 50mm x 15mm

 $(L \times W \times T)$

18 heated zones, 9 top and 9 bottom.

High throughout capability.


Excellent energy efficiency and short heat up times.

■ Fitted with HawkEye 1700 for up to

100% paste on pad inspection.



Surface Mount Line 2



Item	Stencil Printer
Manufacturer	ASM (formally DEK)
Description	Horizon 03iX



Specification

- Stencil printer for 23" or 29" frames, with camera fiducial alignment.
- Fitted with HawkEye 1700 for up to 100% paste on pad inspection.

Item	SMT Pick & Place
Manufacturer	Panasonic
Description	NPM-W2 x 2



Specification

Optically aligned flexible placement;

- Down to 01005"
- Including, BGA, uBGA, QFN, CSP
- Up to 100mm x 50mm x 15mm (L x W x T)

Item	Reflow Oven
Manufacturer	Heller
Description	1809 MkIII

Heller 1809 MKIII



Specification

- Integrated software with zone and profile control for optimal PCB reflow of almost any design
- 18 heated zones, 9 top and 9 bottom.
- Excellent energy efficiency and short heat up times.
- High throughout capability.

Item	PCB Handling
Manufacturer	Nutek
Description	Loaders & conveyors

Unloader



Specification

 Loader/loader, linking conveyors and unloader for full PCB assembly automation.

Maximum PCB Length	Part Number Capacity	Components Per Hour
500mm	213	110,000



Automated Optical Inspection (AOI)

Item Automated Optical Inspection (AOI)


Manufacturer MEK

Description MEK PowerSpector FDAz 650L




Specification

- AOI with 18.75u HD Camera with telecentric optics and eight off 10u side cameras for side and edge inspection of components.
- Omnidirectional multi angle, multi-colour LED lighting with the capability to test a range of criteria on all types of solder joints.
- 1 camera with top side clearance of 30mm.
- Maximum PCB size = 650mm x 550mm



Combined with the central camera this provides a top down view for standard inspection and 8 side views.



550 BTL with top & bottom cameras, for double sided inspection at the same time.



 Item
 Automated Optical Inspection (AOI)

 Manufacturer
 MEK

 Description
 MEK PowerSpector GTAz+GDAz 550BTL



Specification

- AOI with two 18.75u HD Camera with telecentric optics and eight off 10u side cameras for side and edge inspection of components.
- Omnidirectional multi angle, multi-colour LED lighting with the capability to test a range of criteria on all types of solder joints.
- 2 cameras;
 - Top side, clearance = 30mm
 - Bottom side, clearance = 60mm
 - For inspection of both sides of a PCB at the same time.
- Maximum PCB size = 550mm x 550mm



Aqueous PCB Cleaning

 Item
 PCB Cleaning Machine

 Manufacturer
 Trident

 Description
 Trident ZDO



Specification

The Trident ZDO is a batch load PCB cleaning machine, which offers;

- A closed-loop (Zero Discharge Wash Cycle) providing excellent environmental benefits.
- Automatic Wash, Rinse and Dry Cycles.
- Built-In Programmable Cleanliness Verification Testing via a resistivity meter.
- Adjustable board racks to hand PCBs up to 600mm in length.
- Spray in air cleaning system with oscillating basket.

Additional Equipment

In Circuit Test

Item	In Circuit Test Machine
Manufacturer	HP / Agilent
Description	3070 Series 3



Specification

- In Circuit Test (ICT) machine for use with custom test jigs to provide in circuit test of any Printed Circuit Board Assembly (PCBA).
- Functional testing could also be added to the process if applicable.
- Suitable high volume repeatable assemblies.



Support Equipment

ItemThermal ProfilerManufacturerSolderstarDescriptionPRO Profiler R-0625P 6 Channel



Item	Soldering Irons
Manufacturer	Metcal
Description	MFR-1100 Series



Specification

- 6 channel reflow oven profiler.
- Used for optimal product profiling.

Specification

Soldering irons with cartridge tip, which utilises Metcal' SmartHeat® Technology which means;

- They are incapable of overshoot
- They do not need any calibration, ever
- They deliver high throughput at lower temperatures

Plus a range of additional equipment to aid and support the production process, including;

- Wire and cable assembly equipment.
- A range of test equipment.
- Personal operator Bofa bench extraction.
- Support software covering MRP, engineering and programming.